

SIMPLE AND DURABLE

MACHINERY



**Ivo Ozolins**  
Sales Manager  
T.: +371 26383919  
Email: ivo@uotforest.com

**Ugis Ozolins**  
Chairman  
Production Manager  
T.: +371 29369559  
Email: ugis@uotforest.com

[www.uotforest.com](http://www.uotforest.com) / [info@uotforest.com](mailto:info@uotforest.com)

UOTFOREST.COM



SIMPLE AND DURABLE

MACHINERY





**UOU-3000**

**Information:**

The heavy duty forest disc trencher is intended for professionals - contractors and forest managers who appreciate the quality and speed. The trencher is equipped with automatic control. The operator in the tractors cabin can easily change operating modes, depending on the soil type. Disc teeth are made of wear resistant steel and are changeable. UOT-3000 is designed to be attached on forwarder, skidder and harvester tractors.

**Specification:**

Automatic control;  
Weight - 3000 kg;  
Diameter of disc - 140 cm;  
Hydraulic oil flow 100 l / min;  
Prepare able area - an average of 1 ha per hour.



**UOT-2000**

**Information:**

A professional forest soil preparation disc trencher designed to be attached on forestry use agricultural tractors with ability to provide the hydraulic oil flow of 65 l / min. We have developed a technology that in combination with a powerful hydraulic motors, allowing this "lightweight" trencher to be loaded up to 6 ton pressure on the soil under the weight of the tractor.

**Specification:**

Weight - 1200 kg;  
Diameter of the disc - 120 cm;  
The number of teeth - 10;  
Adjustable distance between rows;  
Floating / hydraulic push down option;  
Hydraulic disk drive;  
Hydraulic oil flow 65 l / min;  
Prepare able area - an average of 0.75 ha per hour.



**UOT-1000**

**Information:**

The ideal product to equip forestry use agricultural tractors. We have developed a technology that in combination with a powerful hydraulic motors, allowing this "lightweight" trencher to be loaded up to 3 ton pressure on the soil under the weight of the tractor. The necessary hydraulic oil flow for trenchers operation is only from 50 l / min.

**Specification:**

Weight - 1000 kg;  
Diameter of the disc - 110 cm;  
The number of teeth - 10;  
Adjustable distance between rows;  
Floating / hydraulic push down option;  
Hydraulic disk drive;  
Hydraulic oil flow 50 l / min;  
Prepare able area - an average of 0.6 ha per hour.



**UOT-500**

**Information:**

Forest soil preparation single disc trencher, which is equipped with powerful UOT-1000 hydraulic motor. The necessary hydraulic oil flow for trenchers operation is only from 30 l / min.

**Specification:**

Weight - 420 kg;  
Diameter of the disc - 110 cm;  
The number of teeth - 10;  
Hydraulic push down option;  
Hydraulic oil flow 30 l / min;  
Adjustable trenchers disc angle  
Prepare able area - an average of 0.3 ha per hour.

